

CITIZEN

High speed, LCD control POS printing

Retail class leader

Customisable LCD display

With the ability to add company logos and scrolling messages, the POS printing experience can be personalised to any business' requirements. Printer managers can programme the printer to display specific messages to make everyday operation even easier – low paper warnings, error messages and even instructions on how to order more receipt rolls – whatever the user deems relevant to their printing processes.

In a hurry?

With 500mm/sec. print speed the CT-S801III is the fastest POS printer in the market.



CT-S801III

POS, Receipt printer (thermal 3 inch / 80mm)

Applications

- Hospitality
- Kiosk
- Kitchen
- Retail



Usability, reliability and outstanding performance

TOMORROW'S PRINTING TODAY

Specifications

Model	CT-S801III
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	500mm/sec
Print Width (maximum)	80 mm
Media Width (min to max)	58 / 60 / 80 / 82.5 mm
Roll Size (max), Core Size	83 mm outside diameter
Media Thickness (min to max)	65 to 75 µm or 75 to 85 µm
Main Interface	USB 2.0 full speed
Optional interfaces	Serial (RS-232C compliant), Ethernet + USB host, Powered USB, Ethernet, Bluetooth with Apple™ MFi compatibility, Parallel (IEEE 1284 compliant), USB with hub
Power supply	110 - 240 V, 50/60 Hz
Reliability	200 Million pulses or 150 Km, 2 million cuts
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	145x192x148 mm, 2 Kg, DC version 145x192x120, 1.6 Kg
Cutter	Guillotine type, full and partial
Warranty	2 years including head and cutter
EMC and safety standards	CE, TUV, UL, C-UL, FCC class A, VCCI

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-S801III

POS, Receipt printer (thermal 3 inch / 80mm)

Features & Benefits

- Paper exit: Top exit - ideal for all retail applications
- Paper load: Easy paper loading
- Printing Speed: Ultra fast print out - up to 500mm per second
- Display: LCD display for easy configuration and operation
- Low space requirement - integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification - built-in buzzer
- ENERGY STAR® compliant
- Small footprint
- Recyclable packacking
- Print, Sleep and Standby modes
- Tool-free maintenance